



FIRE RESISTANT TIMBER FIRE DOORS

Certificate number: FRTD 410

This is a product certificate to certify that

Halspan Limited

Muirhouses, Bo'ness,
Edinburgh. EH51 9SS

Tel: +44 (0) 1506 827538 Fax: +44 (0) 1506 825996

E-mail: doors@halspan.com Web: www.halspan.com

Who supply door blanks for the manufacture of the following fire doors & doorsets:

| | |
|------------------------------------|-----------------------------|
| Halspan Optima FD30 | Halspan Optima FD60 |
| Halspan Prima FD30 | Halspan Prima FD60 |
| Halspan Panelled Prima/Optima FD30 | Halspan Panelled Prima FD60 |
| Halspan FD90 | Halspan FD120 |
| Halspan Prima Plus FD30 | Halspan Prima Plus FD60 |
| Halspan Prima Plus FD90 | Halspan Prima Plus FD120 |
| Halspan Prima Plus Enhanced FD60 | |

have satisfied the requirements of the scheme SDP01. This includes the testing of products to **BS476: Part 22**, the inspection of Factory Production Control and continuing surveillance audits and testing of samples of products taken from production. The product specification and field of application to achieve from 30 minutes to 120 minutes integrity are detailed on page 2 of this certificate.



First Issued: 1 February 2006

Reissued: 1 February 2012

Revised: 01 November 2018

Valid to: 31 January 2022

Issue No: 11



175

Ian Woodhouse
Director of Certification

IFC Certification Ltd, 20 Park Street, Princes Risborough, Buckinghamshire. UK, HP27 9AH
Tel: +44 (0)1844 275500 Fax: +(0)1844 274002 E-mail: info@ifccertification.com Web: www.ifccertification.com
Registered No: 4777898 England

The certificate and schedule are held in force by regular annual surveillance visits by IFC Certification and the reader or user should contact IFC Certification to validate its status. This certificate remains the property of IFC Certification and must be returned to them on demand.



Certificate number: FRTD 410

The production of fire resistant timber doorsets are manufactured in accordance with assessment/ test reports referenced within the following table:

| Description | Fire Rating | Assessment/ Test Report |
|-------------------------------|--------------------|--------------------------------|
| Halspan Prima | FD30 | 06166B (HS01) |
| Halspan Prima | FD60 | 06167C (HS02) |
| Halspan Optima | FD30 | PAR/10341/01 Rev A (HS03) |
| Halspan Optima | FD60 | PAR/10341/02 Rev B (HS04) |
| Halspan Panelled Prima/Optima | FD30 | FEA F97097 Rev I |
| Halspan Panelled Prima | FD60 | A01015 Rev D |
| Halspan | FD90 | PAR/10513/01 Rev A (HS05) |
| Halspan | FD120 | PAR/10513/02 Rev A (HS06) |
| Halspan Prima Plus | FD30 | IFCA/15953/01 |
| Halspan Prima Plus | FD60 | IFCA/15953/02 |
| Halspan Prima Plus | FD90 | PAR/17519/01 |
| Halspan Prima Plus | FD120 | PAR/17519/02 |
| Halspan Prima Plus Enhanced | FD60 | PAR/16286/01 |

The scope of the certification is limited to the details and parameters contained within these reports and all aspects of the specification and limitations defined therein must be satisfied.

It is the certificate holder's responsibility to ensure that the latest version/ revision of the above assessment reports are maintained as part of the audited FPC system.

Failure to comply with all specifications will invalidate the certification and may jeopardise the fire performance.

The certificate and schedule are held in force by regular annual surveillance visits by IFC Certification and the reader or user should contact IFC Certification to validate its status. This certificate remains the property of IFC Certification and must be returned to them on demand.