

## **Schedule No. MS01**

**for the fabrication of fire resistant timber doorsets  
utilising fire door blanks  
in accordance with field of application /  
global assessment reports as detailed in the table below**

<b>FireSmoke FD30</b>	<b>PAR/12519/01 Rev D</b>
<b>FireSmoke FD60</b>	<b>PAR/12519/02 Rev D</b>
<b>FireSound FD30 &amp; FD60</b>	<b>PAR/12519/03 Rev E</b>
<b>FireSmoke FD30 with Side &amp; OP</b>	<b>PAR/14247/01</b>
<b>FireSound 44mm FD30</b>	<b>PAR/14559/01</b>
<b>FireSound 59mm FD90</b>	<b>PAR/15143/01 Rev A</b>
<b>Ferro Firesafe 68-98mm FD30</b>	<b>PAR/13145/01</b>

***The above referenced Field of Application assessment reports cover a number of different door leaf designs in various commercially available configurations. The scope of the certification is limited to the details and parameters contained within these reports.***

This schedule must be read in conjunction with the above mentioned Field of Application reports and Global Assessments and all aspects of the specification and limitations defined therein must be satisfied. Failure to comply with all specifications will invalidate the approval, and may jeopardise the fire performance.



**Ian Woodhouse  
Director**

**Date: 23 April 2018  
Revised: 11 July 2018**

---

The certificate and schedule are held in force by regular annual surveillance visits by IFC Certification and the reader or user should contact IFC Certification to validate its status. This certificate remains the property of IFC Certification and must be returned to them on demand.

©IFC Certification Ltd