



ACOUSTIC PERFORMANCE

Supplement 13/01 to Certificate FRTD 446

Issued to

Nea Stereotis Ltd

Larnaca Free Trade Zone
P O Box 42045
6530 Larnaca
Cyprus

44mm Halspan Prima/Optima Single Leaf up to 34dB Rw(glazed)
44mm Halspan Prima/Optima Single Leaf up to 32dB Rw(unglazed)
54mm Halspan Prima/Optima Single Leaf up to 36dB Rw (glazed)
54mm Halspan Prima/Optima Single Leaf up to 34dB Rw (unglazed)
44mm/54mm Halspan Prima/Optima Double Leaf up to 35dB Rw(glazed)
64mm Halspan FD90 Single Leaf up to 36 dB Rw (unglazed)
64mm Halspan FD120 Single Leaf up to 39 dB Rw (unglazed)
64mm Halspan FD120 Double Leaf up to 39 dB Rw (unglazed)

This addendum certifies the acoustic performance of the above doors in accordance with BS EN 10140-2:2010. **To provide the performance indicated above the specification given in the 'Halspan Technical Support Manual- Acoustic Information' should be followed.**

For combined fire and acoustic performance this addendum and referenced documentation should be read in conjunction with Certificate FRTD 446 and associated documentation.

A handwritten signature in black ink, appearing to read 'Ian Woodhouse'.

Ian Woodhouse
Director of Certification

Issued: 26 September 2013
Re-issued: 08 August 2016
Valid to: 07 August 2021

IFC Certification Ltd, 20 Park Street, Princes Risborough, Buckinghamshire, HP27 9AH, UK,
Tel: +44 (0)1844 275500 Fax: +(0)1844 274002 E-mail: info@ifccertification.com Web: www.ifccertification.com
Registered No: 4777898 England

The certificate and schedule are held in force by regular annual surveillance visits by IFC Certification and the reader or user should contact IFC Certification to validate its status. This certificate remains the property of IFC Certification and must be returned to them on demand.