



ACOUSTIC PERFORMANCE

Supplement to Certificate IFCC1317

Issued to

Kataskevi Portas A Porta Ltd

NEA Monastiriou 59 Eleftherio
Thessaloniki
56334
Greece

44mm Halspan Prima/Optima Single Leaf up to 34dB Rw(glazed)
44mm Halspan Prima/Optima Single Leaf up to 32dB Rw(unglazed)
54mm Halspan Prima/Optima Single Leaf up to 36dB Rw (glazed)
54mm Halspan Prima/Optima Single Leaf up to 34dB Rw (unglazed)
44mm/54mm Halspan Prima/Optima Double Leaf up to 35dB Rw(glazed)
64mm Halspan FD90 Single Leaf up to 36 dB Rw (unglazed)
64mm Halspan FD120 Single Leaf up to 39 dB Rw (unglazed)
64mm Halspan FD120 Double Leaf up to 39 dB Rw (unglazed)

This addendum certifies the acoustic performance of the above doors in accordance with BS EN 10140-2:2010. **To provide the performance indicated above the specification given in the 'Halspan Technical Support Manual- Acoustic Information' should be followed.**

For combined fire and acoustic performance this addendum and referenced documentation should be read in conjunction with Certificate IFCC1317 and associated documentation.

A handwritten signature in black ink, appearing to read 'Ian Woodhouse'.

Ian Woodhouse
Director of Certification

First Issued: 21 August 2017
Reissued: 2 August 2018
Valid to: 20 August 2019

IFC Certification Ltd, 20 Park Street, Princes Risborough, Buckinghamshire. UK, HP27 9AH
Tel: +44 (0)1844 275500 Fax: +(0)1844 274002 E-mail: info@ifccertification.com Web: www.ifccertification.com
Registered No: 4777898 England

The certificate and schedule are held in force by regular annual surveillance visits by IFC Certification and the reader or user should contact IFC Certification to validate its status. This certificate remains the property of IFC Certification and must be returned to them on demand.