



FIRE RESISTANT TIMBER DOOR SCHEME

Certificate number: IFCC 1545

Certificate only valid if verified on website - www.ifccertification.com

This is a product certificate to certify that

Weng Meng Industries Sdn Bhd

No.11, Jalan 8, Kompleks Perabot Olak Lempit, 42700 Banting,
Selangor, Malaysia

Tel: +603 3149 1188

Who fabricate the following timber fire doors and or doorsets:

Halspan FD30, FD60, FD90 & FD120
WMI Sandor FFGV FD30, PMFD FD30 & Pattern 10 FD30
WMI Sandor Composite FD30, FD60, FD90 & FD120
Strebord FD30, FD60, Stredor FD60, Ramkor FD60, FD90 Plus &
Ramkor FD120 Plus, Duocore FD30, Trisound FD30, FD60
Warmsprings FD60, FD90, FD120 & Flamebreak FD30, FD60

have satisfied the requirements of the SDP01 Fire resistant Timber Door scheme. This includes the testing of products to **BS476: Part 22**, the inspection of Factory Production Control and continuing surveillance audits and testing of samples of products taken from production. The product specification and field of application to achieve from **30 minutes to 120 minutes integrity** are detailed on page 2 & 3 of this certificate.



Initial certification: 3 January 2020
Re-issued: 6 February 2020
Revised: 3 May 2022
Valid to: 2 January 2025
Issue status: 4



175

Ian Woodhouse
Director of Certification

Certificate number: IFCC 1545

The production of fire resistant timber doorsets are manufactured in accordance with assessment/ test reports referenced within the following table:

Doorset Description	Fire Rating	Assessment/ Test Report
Sandor Flush Fire Rated Door Leaves Set with Composite Core installed in Timber/Metal * Frames. <ul style="list-style-type: none"> · Series FFRD.E30F · Series FFRD.E60F · Series FFRD.E90F · Series FFRD.E120F <i>*(Only FD120 tested in Metal Frame)</i>	FD30, FD60, FD90, FD120	WF406295 WF406296
Sandor Flush Fire Rated Door Leaves Set with Timber Inserts and Composite Core installed with Timber Frame. <ul style="list-style-type: none"> · Series FFGV.FD30 	FD30	EWA 27327-05
Sandor Decorative Panelled Fire Rated Door Leaves Set with Composite Core installed with Timber Frame. <ul style="list-style-type: none"> · Series PMFD.FD30 · Series Pattern 10.FD30 	FD30	WF414872/WF332900 WF332901
Halspan Optima	FD30	HS03 PAR/10341/01 B
Halspan Optima	FD60	HS04 PAR/10341/02 B
Halspan Prima	FD30	HS01 06166C
Halspan Prima	FD60	HS02 06167C
Halspan	FD90	HS05 PAR/10513/01 A
Halspan	FD120	HS06 PAR/10513/02 B
Prima Plus	FD30	PAR/15953/01
Prima Plus	FD60	IFCA/15953/02
Prima Plus	FD90	PAR/17519-01
Prima Plus	FD120	PAR/17519-02
Prima Plus Enhanced	FD60	PAR/16286-01
Halspan 30 Panelled Prima/Optima	FD30	FEA/F97097 Rev I
Halspan 60 Panelled Prima	FD60	Chilt A01015 Rev D
Strebord	FD30	IFCA/08037
Strebord 44	FD30	Chilt/A02066
Strebord 44+	FD30	WF417523
Strebord 54	FD60	Chilt/A02067
Strebord 54 Panelled	FD60	Chilt/A10152
Stredor 44	FD30	BMT/CAN/F15159
Stredor 54	FD60	WF377027
Strebord 44/54 and Stredor 44/54	FD30	WF407090
Strebord 54 and Stredor 54	FD60	WF427764

The certificate and schedule are held in force by regular annual surveillance visits by IFC Certification and the reader or user should contact IFC Certification to validate its status. This certificate remains the property of IFC Certification and must be returned to them on demand.

Certificate number: IFCC 1545

Duocore 44	FD30	Chilt/A12296
Trisound	FD30	PAR/12033/01
Trisound	FD60	PAR/13088/01
Strebord LUX	FD30	PAR/20276/01
Ramkor	FD60, FD90	PAR/17082/01
Ramkor 90/90+	FD90	WF383876 PAR/17082/01
Ramkor 120	FD120	PAR/19681/01
WSCP Fire Resisting Doorsets	FD60, FD90 & FD120	Chilt/A12138 IFCA/07019
Flamebreak	FD30	FEA/98164
Flamebreak	FD60	FEA/F02141

The scope of the certification is limited to the details and parameters contained within these reports and all aspects of the specification and limitations defined therein must be satisfied.

It is the certificate holder's responsibility to ensure that the latest version/ revision of the above assessment reports are maintained as part of the audited FPC system.

Failure to comply with all specifications will invalidate the certification and may jeopardise the fire performance.