



ACOUSTIC PERFORMANCE

Supplement 13/01 to Certificate IFCC1269

Issued to

Eurodoor OOD

Rupite
Petrich 8426
Bulgaria

Tel: +302 3210 51049

- 44mm Halspan Prima/Optima Single Leaf** up to 34dB Rw(glazed)
- 44mm Halspan Prima/Optima Single Leaf** up to 32dB Rw(unglazed)
- 54mm Halspan Prima/Optima Single Leaf** up to 36dB Rw (glazed)
- 54mm Halspan Prima/Optima Single Leaf** up to 34dB Rw (unglazed)
- 44mm/54mm Halspan Prima/Optima Double Leaf** up to 35dB Rw(glazed)
- 64mm Halspan FD90 Single Leaf** up to 36 dB Rw (unglazed)
- 64mm Halspan FD120 Single Leaf** up to 39 dB Rw (unglazed)
- 64mm Halspan FD120 Double Leaf** up to 39 dB Rw (unglazed)

This addendum certifies the acoustic performance of the above doors in accordance with BS EN 10140-2:2010. **To provide the performance indicated above the specification given in the 'Halspan Technical Support Manual- Acoustic Information' should be followed.**

For combined fire and acoustic performance this addendum and referenced documentation should be read in conjunction with Certificate IFCC1269 and associated documentation.

A handwritten signature in black ink, appearing to read 'Ian Woodhouse'.

Ian Woodhouse
Director of Certification

Issued: 05 October 2016
Valid to: 04 October 2017

IFC Certification Ltd, 20 Park Street, Princes Risborough, Buckinghamshire, HP27 9AH, UK,
Tel: +44 (0)1844 275500 Fax: +(0)1844 274002 E-mail: info@ifccertification.com Web: www.ifccertification.com
Registered No: 4777898 England

The certificate and schedule are held in force by regular annual surveillance visits by IFC Certification and the reader or user should contact IFC Certification to validate its status. This certificate remains the property of IFC Certification and must be returned to them on demand.